



**Kyutech**

Kyushu Institute of Technology

国立大学法人

九州工業大学



**La SEINE**

# Link Budget

## Telemetry & Missions data

---

BIRDS-X

Date: 2023/03/17

For public use

# Uplink

PARAMETERS		
Objective		APRS-Digipeater and Store and Forward Mission
Frequency	[MHz]	145.825
Emission Type		15K0F2D
Modulation		AFSK
Data Rate	[bps]	1200
Protocol		AX.25
GROUND STATION		
Ground Station Transmitter Power Output	[W]	50.0
	[dBw]	17.0
Ground Station Total Transmission Line Losses	[dB]	1.5
Antenna Gain	[dBi]	16.0
Ground Station EIRP	[dBw]	31.5
UPLINK PATH		
Orbit Altitude	[km]	400
Elevation Angle	[degree]	10.0
Slant Range	[km]	1439.8
Ground Station Antenna Pointing Loss	[dB]	1.0
Ground Station to Spacecraft Antenna Polarization Loss	[dB]	3.0
Path Loss	[dB]	138.9
Atmospheric Losses	[dB]	1.1
Ionospheric Losses	[dB]	0.7
Rain Losses	[dB]	0.0
Isotropic Signal Level at Spacecraft	[dBw]	-113.2
SPACECRAFT (RX Power Sensitivity Method)		
Spacecraft Antenna Pointing Loss	[dB]	5.0
Spacecraft Antenna Gain	[dBi]	2.2
Spacecraft Total Transmission Line Losses	[dB]	2.3
Signal Power at Spacecraft LNA Input	[dBw]	-118.4
	[dBmW]	-88.4
Required Signal Power at Spacecraft LNA Input	[dBmW]	-105.0
System Link Margin	[dB]	16.6

# Downlink

PARAMETERS				
Objective		Telemetry and other Mission Data (UHF1,2)	CW Beacon	APRS-Digipeater and Store and Forward Mission
Frequency	[MHz]	437.375	437.375	145.825
Emission Type		8K50F1D	500HA1A	15K0F2D
Modulation		GMSK	Morse Code	AFSK
Data Rate	[bps]	4800	20 wpm	1200
Protocol		AX.25	-	AX.25
SPACECRAFT				
Spacecraft Transmitter Power Output	[W]	0.8	0.1	2.0
	[dBw]	-1.0	-10.0	3.0
Spacecraft Total Transmission Line Losses	[dB]	3.0	3.0	2.3
Spacecraft Antenna Gain	[dBi]	2.2	2.2	2.2
Spacecraft EIRP	[dBw]	-1.8	-10.9	2.8
DOWNLINK PATH				
Orbit Altitude	[km]	400	400	400
Elevation Angle	[degree]	10.0	10.0	10.0
Slant Range	[km]	1439.8	1439.8	1439.8
Spacecraft Antenna Pointing Loss	[dB]	5.0	5.0	5.0
Spacecraft-to-Ground Antenna Polarization Loss	[dB]	3.0	3.0	3.0
Path Loss	[dB]	148.4	148.4	138.9
Atmospheric Losses	[dB]	1.0	1.0	1.1
Ionospheric Losses	[dB]	0.4	0.4	0.7
Rain Losses	[dB]	0.0	0.0	0.0
Isotropic Signal Level at Ground Station	[dBw]	-159.6	-168.7	-145.9
GROUND STATION (SNR Method)				
Ground Station Antenna Pointing Loss	[dB]	1.0	1.0	1.0
Ground Station Antenna Gain	[dBi]	22.0	22.0	16.0
Ground Station Total Transmission Line Losses	[dB]	3.4	3.4	1.5
Ground Station Effective Noise Temperature	[K]	1000.0	1000.0	1000.0
Signal Power at Ground Station LNA Input	[dBw]	-142.0	-151.1	-132.4
Ground Station Receiver Bandwidth	[Hz]	15000.0	500.0	15000.0
Ground Station Receiver Noise Power	[dBw]	-156.8	-171.6	-156.8
Signal-to-Noise Power Ratio (SNR) at Ground Station Receiver	[dB]	14.8	20.5	24.5
Required SNR for Ground Station receiver	[dB]	10.6	10.0	11.5
System Link Margin	[dB]	4.2	10.5	13.0

